

ASPHALT & TARMAC RESTORER

PRODUCT DESCRIPTION

- ProtectiT Asphalt & Tarmac Restorer is a water based high performance sealer developed specifically for asphalt, tarmac and concrete surfaces.
- It restores the look of tired and worn tarmac/asphalt to a new finish and is very easy to apply.
- Once dried the product enhances the waterproof protection whilst providing a low sheen.

SURFACE PREPARATION

Surface needs to be dry and free from dirt, loose material, moss and algae. Use an appropriate fungicidal wash before applying. Oil and grease deposits should be removed using Protectit Oil Off. It is important to remove all coatings and sealers.

APPLICATION

Always carry out a test area first to ensure the finished result is acceptable.

- Product supplied ready to use and should not be diluted. Shake the container well before use.
- Apply using a long pile roller or soft brush spreading over the surface at a rate of 4-6m²/ltr depending on surface condition.
- Allow to dry for 2-4 hours then apply a second coat.
- DO NOT use any vehicles on the restored surface for a minimum of 24 hours following application.
- Drying time is 24 hours from final application.
- Remove as much product as possible from tools and clean immediately with soapy water.

COVERAGE

1 Litre covers 4 - 6m² (depending on porosity and texture of the surface)

SHELF LIFE & STORAGE

24 months from the date of manufacture in the original unopened container. Store locked up in dry place between 5°C and 25°C in the original container.

Important: The content of this documentation is based on our experience of the product. PROTECTiT SP guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with PROTECTiT SP products or bad weather conditions.

KEY FEATURES

- Restores the look of tired and worn tarmac, asphalt and concrete
- Excellent protection against weather
- Resists growth of fungal and algae
- Improves slip resistance



PRECAUTIONS FOR USE

Do not apply in wet weather or if rain is forecast within 24 hours following final coat application. Do not apply to newly laid tarmac/asphalt for a minimum of 60 days or newly laid concrete within a minimum of 30 days. Always keep pets and children away until surface is fully dry. Do not apply when surface temperature is below 10°C or above 25°C.

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).