

GRAFFITI REMOVER

PRODUCT DESCRIPTION

- Graffiti Remover is a powerful solvent based, activated product for removal of graffiti from painted and non-painted substrates.
- Easy and quick to use, suitable for exterior and interior use on floors & walls. Product is suitable for porous and non porous surfaces, metal, glass and rubber.
- ProtectiT Graffiti Remover is used by local authorities, bus and rail companies and on heritage projects.

IMPORTANT BEFORE USE

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption. Ensure the surface(s) to be clean are dry before applying the product.

Do not apply during rain or frost and when surface air temperature is <7°C and >30°C. Do not apply in direct sunlight.

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

APPLICATION

Always test a small area before proceeding to ensure finished result is acceptable.

- Optimum performance is reached between 7°C and 30°C. Do not use in wet weather or if rain is forecast. Graffiti Remover is supplied ready to use and should not be diluted.
- Ensure the surface is dry and apply a generous even coat.
- Allow the Graffiti Remover to work leaving for the following recommended times:
 - **Spray paint and pen on non porous surface:** up to 5 minutes.
 - **Spray paint and pen on porous surface:** up to 30 minutes.
- Agitate with a stiff brush and rinse clean, alternatively use a power washer.
- If a shadow or mark remains use ProtectiT Deep Cleaner.
- Remove as much product as possible from tools and clean immediately with soapy water.

KEY FEATURES

- Fast & effective remover
- Easy to use, non caustic
- Removes all types of graffiti from porous and non porous surfaces
- Does not damage natural & sensitive surfaces including granite or marble
- ProtectiT Graffiti Remover is used by local authorities, bus and rail companies and on heritage projects.



TECHNICAL DATA

- **Colour:** Clear
- **Odour:** Characteristic
- **Form:** Liquid
- **Coverage:** 2-5 m² per litre. Dependant on the porosity of the surface.
- **PH:** 4.5
- **Specific Gravity @ 25°C:** 1.00
- **Application Temperatures:**
 - Minimum +5°C
 - Maximum 30°C

Important: The content of this documentation is based on our experience of the product. PROTECTiT SP guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with PROTECTiT SP products or bad weather conditions.